

Package: weightedGCM (via r-universe)

October 4, 2026

Type Package

Title Weighted Generalised Covariance Measure Conditional Independence Test

Version 0.1.2

Description A conditional independence test that can be applied both to univariate and multivariate random variables. The test is based on a weighted form of the sample covariance of the residuals after a nonlinear regression on the conditioning variables. Details are described in Scheidegger, Hoerrmann and Buehlmann (2022) ``The Weighted Generalised Covariance Measure" <<http://jmlr.org/papers/v23/21-1328.html>>. The test is a generalisation of the Generalised Covariance Measure (GCM) implemented in the R package 'GeneralisedCovarianceMeasure' by Jonas Peters and Rajen D. Shah based on Shah and Peters (2020) ``The Hardness of Conditional Independence Testing and the Generalised Covariance Measure" <[doi:10.1214/19-AOS1857](https://doi.org/10.1214/19-AOS1857)>.

License GPL-2

Imports methods, mgcv, stats, xgboost (>= 3.1.2.1)

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

Encoding UTF-8

Config/roxygen2/version 8.1.0

NeedsCompilation no

Author Cyrill Scheidegger [aut, cre, cph], Julia Hoerrmann [ths], Peter Buehlmann [ths], Jonas Peters [ctb, cph] (Parts of the code are inspired by similar functions from the R package 'GeneralisedCovarianceMeasure' by Jonas Peters and Rajen D. Shah), Rajen D. Shah [ctb, cph] (Parts of the code are inspired by similar functions from the R package 'GeneralisedCovarianceMeasure' by Jonas Peters and Rajen D. Shah)

Maintainer Cyrill Scheidegger <cyscheidegger@gmail.com>

Config/pak/sysreqs make
Repository <https://cyrillsch.r-universe.dev>
Date/Publication 2026-09-04 09:45:50 UTC
RemoteUrl <https://github.com/cran/weightedGCM>
RemoteRef HEAD
RemoteSha db3c1f74f4530046946cbb3f5e87b3dfb4e94828

Contents

wgcm.est	2
wgcm.fix	3
Index	5

wgcm.est	<i>Weighted Generalised Covariance Measure (WGCM) With Estimated Weight Function Conditional Independence Test</i>
----------	--

Description

The Weighted Generalised Covariance Measure (WGCM) with Estimated Weight Function is a test for conditional independence. It is a generalisation of the Generalised Covariance Measure implemented in the R package GeneralisedCovarianceMeasure.

Usage

wgcm.est(X, Y, Z, beta = 0.3, regr.meth, regr.pars = list(), nsim = 499)

Arguments

X	A (n x d_X) numeric matrix with n observations of d_X variables.
Y	A (n x d_Y) numeric matrix with n observations of d_Y variables.
Z	A (n x d_Z) numeric matrix with n observations of d_Z variables.
beta	A real number between 0 and 1 indicating the fraction of the sample used to estimate the weight function.
regr.meth	One of "gam" and "xgboost" indicating the regression method used to estimate the conditional expectations E[X Z] and E[Y Z] and the weight function sign(E[(X-E[X Z])(Y-E[Y Z]) Z]).
regr.pars	Optional additional regression parameters if 'regr.meth == "xgboost"': can specify 'max_nrounds', 'k_cv', 'early_stopping_rounds', and vectors 'eta' and 'max_depth'.
nsim	Number of samples used to calculate the p-value using simulation. Only used if max(d_X, d_Y) > 1.

Value

A p-value for the null hypothesis of conditional independence of X and Y given Z.

References

Please cite the following papers. Cyrill Scheidegger, Julia Hoerrmann, Peter Buehlmann: "The Weighted Generalised Covariance Measure" <<http://jmlr.org/papers/v23/21-1328.html>>

Rajen D. Shah, Jonas Peters: "The Hardness of Conditional Independence Testing and the Generalised Covariance Measure" <[doi:10.1214/19-AOS1857](https://doi.org/10.1214/19-AOS1857)>

Examples

```
set.seed(1)
n <- 200
Z <- rnorm(n)
X <- Z + 0.3*rnorm(n)
Y1 <- Z + 0.3*rnorm(n)
Y2 <- Z + 0.3*rnorm(n) + 0.3*X
Y3 <- Z + 0.3*rnorm(n) + 0.15*X^2
wgcm.est(X, Y1, Z, beta = 0.3, regr.meth = "gam")
wgcm.est(X, Y2, Z, beta = 0.3, regr.meth = "gam")
wgcm.est(X, Y3, Z, beta = 0.3, regr.meth = "gam")
```

wgcm.fix

*Weighted Generalised Covariance Measure (WGCM) With Fixed
Weight Functions Conditional Independence Test*

Description

The Weighted Generalised Covariance Measure (WGCM) with Fixed Weight Functions is a test for conditional independence. It is a generalisation of the Generalised Covariance Measure implemented in the R package GeneralisedCovarianceMeasure.

Usage

```
wgcm.fix(
  X,
  Y,
  Z,
  regr.meth,
  regr.pars = list(),
  weight.num,
  weight.meth = "sign",
  nsim = 499
)
```

Arguments

<code>X</code>	A (n x d_X) numeric matrix with n observations of d_X variables.
<code>Y</code>	A (n x d_Y) numeric matrix with n observations of d_Y variables.
<code>Z</code>	A (n x d_Z) numeric matrix with n observations of d_Z variables.
<code>regr.meth</code>	One of "gam" and "xgboost" indicating the regression method used to estimate the conditional expectations $E[X Z]$ and $E[Y Z]$.
<code>regr.pars</code>	Optional additional regression parameters if 'regr.meth == "xgboost"': can specify 'max_nrounds', 'k_cv', 'early_stopping_rounds', and vectors 'eta' and 'max_depth'.
<code>weight.num</code>	Number k_0 of weight functions per dimension of Z to be used additionally to the constant weight function $w(z) = 1$. The total number of weight functions will be $1 + k_0 * d_Z$. In case of $\max(d_X, d_Y) > 1$, the same $1 + k_0 * d_Z$ weight functions are used for every combination of the components of X and Y.
<code>weight.meth</code>	String indicating the method to choose the weight functions. Currently, only "sign" is implemented.
<code>nsim</code>	Number of samples used to calculate the p-value using simulation.

Value

A p-value for the null hypothesis of conditional independence of X and Y given Z.

References

Please cite the following papers. Cyrill Scheidegger, Julia Hoerrmann, Peter Buehlmann: "The Weighted Generalised Covariance Measure" <<http://jmlr.org/papers/v23/21-1328.html>>

Rajen D. Shah, Jonas Peters: "The Hardness of Conditional Independence Testing and the Generalised Covariance Measure" <[doi:10.1214/19-AOS1857](https://doi.org/10.1214/19-AOS1857)>

Examples

```
set.seed(1)
n <- 200
Z <- rnorm(n)
X <- Z + 0.3*rnorm(n)
Y1 <- Z + 0.3*rnorm(n)
Y2 <- Z + 0.3*rnorm(n) + 0.3*X
Y3 <- Z + 0.3*rnorm(n) + 0.15*X^2
wgcm.fix(X, Y1, Z, regr.meth = "gam", weight.num = 7, weight.meth = "sign")
wgcm.fix(X, Y2, Z, regr.meth = "gam", weight.num = 7, weight.meth = "sign")
wgcm.fix(X, Y3, Z, regr.meth = "gam", weight.num = 7, weight.meth = "sign")
```

Index

wgcm.est, [2](#)

wgcm.fix, [3](#)